

# NOVAGUARD SILK

ACRYLIC BASED NATURAL WOOD EFFECT SILKY MATT PAINT

## DEFINITION

Acrylic based, waterborne, highly resistant to exterior conditions, silky matt, semi transparent natural wood effect exterior jamb paint.

## PROPERTIES

NOVAGUARD SILK is highly resistant to altering exterior conditions due to its perfect chemical formulation. The general properties are;

- Perfect spreading
- High UV resistance
- High alkali resistance
- Low water absorption
- High scrub resistance

## AREAS OF APPLICATION

NOVAGUARD SILK can be applied onto all interior and exterior wooden surfaces. It can also be applied onto the jambs, concrete panels etc by the special pattern apparatus.

## SURFACE PREPARATION

The surfaces should be cleaned of dust, stain, and impurities. The dusty and weak surfaces should be scratched and cleaned out as well as the swelling and limy surfaces. Decopaste Ext-0100 should be applied in case of a repairment.

## APPLICATION

Before the application of NOVAGUARD SILK, the surfaces should be primed by Byprime, Bytech Concentrated Prime (1/7) and Byprime pigmented (dilution by % 5-10) by roller or airless spray gun as one layer. NOVAGUARD SILK can be applied by brush, roller, sponge, pattern apparatus directly or by spraygun (by diluted to 10 % w/w), after the application of the primer. The cleaning of the equipments should be done by water.

## PACKAGING AND STORAGE

NOVAGUARD SILK is produced in 15/7,5/2,5 kg plastic pails. The goods should be stored in clean and dry areas and kept away from sun, rain, hot and cold weathers. The unsealed goods can be stored for 12 months.

## HEALTH AND SECURITY

S2 Keep out of reach of children.